Thank you for choosing to build your new home at Te Whata Tuarua. As part of the building process, each house design at Te Whata Tuarua will need to be approved by Ngāi Tahu Property prior to work starting on site. To assist in this process, the following Design Guidelines have been developed.

## THE PURPOSE

The purpose of these Guidelines is to help owners and their designers through the house plan approval process and to encourage good design practice. This is important for the overall urban design at Te Whata Tuarua and will help protect and enhance the value of your property.

Please take the time to read the following guide and if you, your designer, or your builder require advice or clarification before submitting plans for approval, please do not hesitate to contact our Residential Sales Manager, Dene Maddren on 021 622 749 or dene.maddren@ngaitahu.iwi.nz.

## **THE PROCESS**

Once you have read the Guidelines and gathered your thoughts about the design of your home, you can have your plans approved:

- 1. As a "Traditional Design" by following the Design Guidelines and demonstrating a high level of compliance to the 'Objectives' and 'Specific Requirements'.
- 2. As an 'Alternative Design' by showing compliance to the 'Objectives' of the Guidelines but not necessarily all the 'Specific Requirements'. This option allows greater flexibility of building forms and materials but requires a higher standard of design as determined by the Developer.

When you are ready to proceed complete the attached Plan Approval Application form and return it with your house plans, exterior colours and landscape plans.

**Please note:** these Guidelines do not in any way replace or compete with the requirements of the Local Authority planning or building consent rules and regulations. The responsibility for compliance and approval with these rules must be considered independently by the designer or owner.

## THE GUIDELINES

## YOUR HOME

#### **SITING**

### **Objectives**

Your home should be designed specifically for your section. It should take into account prevailing winds, sun, outdoor living spaces, vehicle access onto site, and neighbouring dwellings.

## Specific Requirements

- Locate living rooms so that they receive at least 3 hours of sunshine even on the shortest day of the year.
- Kitchens should be located so that they do not receive direct late afternoon sun.
- Appropriately proportioned outdoor living area shall be directly outside this living room with thought given to shelter from prevailing winds.
- Provide for suitable vehicle access to the garage without compromising the outdoor living areas and gardens at the front of your home.
- Corner sections require very careful consideration due to their additional profile on more than one boundary.

#### **BUILDING SIZE**

### **Objectives**

It is important that the completed homes at Te Whata Tuarua are of an appropriate size for the section on which they are to be built.

## Specific Requirements

### The following minimum building sizes are required under these Design Guidelines:

These measurements include garaging if under the main roof.

NETT SECTION SIZE	DWELLING MINIMUM FLOOR AREA
0 - 300 m²	90 m²
301 – 400 m²	110 m²
401 – 500 m²	130 m²
501 – 600 m <sup>2</sup>	150 m²
over - 600 m <sup>2</sup>	170 m²

The <u>nett</u> area refers to the size of a section <u>excluding</u> any right-of-way or common driveway area.

<u>Maximum</u> house sizes are based on a percentage of the <u>nett</u> section area and are set by the <u>Local</u> Authority.

### **BUILDING CHARACTER**

## **Objectives**

Houses at Te Whata Tuarua should be designed to reflect a modern New Zealand character responding to the local climate, environment and lifestyle.

Buildings should relate to the street and any public boundaries maintaining good visual links in order to contribute to the safety of the local community and social interaction.

Roof forms should be strong and simple to help create interest and variety, and front facades should use a limited mixture of materials and colours to provide a strong streetscape.

### Specific Requirements

#### Exterior Appearance

- The garage door should not dominate the street façade but be either set back at least one metre behind the line of the house or aligned at right angles to the street boundary.
- The front door shall be clearly defined and access to the door readily visible from the street frontage.
- The street façade shall be designed with large clear glazed windows or doors to provide a good visual link to the outside. Narrow horizontal windows addressing the street are not considered appropriate.
- Exterior materials should complement the form and style of the house and generally be recognised as local Canterbury materials.
- Changes in exterior materials shall not occur on an outside corner but rather wrap around the corner to a suitable point beyond to maintain the strength of the forms.
- Verandas, pergolas and other forms of sun control are recommended particularly on the North and West elevations.
- Specific 'Optional Height' sites are noted within the development and only these can have a two storey home erected. Subject to criteria noted in the Restrictive Covenants.

#### Roof Forms

- Simple roof forms are recommended. The plan and sections/elevations should relate to each other
  to eliminate small changes in wall lines with the resultant multiplicity of hip ridges and valleys. This
  will result in a better aesthetic result as well as a more cost-effective construction.
- The roof pitch should reflect the style of the house, and be a strong design element.

#### "Traditional Design"

- Houses shall have at least one full structural gable with one end addressing each street frontage, public reserve, and/or other public boundary. The scale of this gable should be significant enough as to not appear like a token gesture.
- The roof pitch shall be between 25° and 40° (apart from roofs over ancillary or linking building elements which can be flat or very low pitched).
- Any gables should preferably carry the gable ridge for the full length (or at least 75%) of the space below, or the primary building element.
- Roof eaves shall have a minimum 300mm overhang to protect against summer sun in the habitable rooms and to improve weather tightness.

### "Alternative Design"

- A high standard of professional design input needs to be demonstrated.
- The proportion of solid to void spaces needs to be carefully considered and resolved so that the overall modelling is clear and strong.

- The roof form needs to reflect and respond to this modelling.
- Low monopitch roofs shall have a minimum pitch of 8°.
- Any parapets need to be resolved in three dimensions to fully conceal flat roof elements.
- Appropriate solar screening needs to be provided particularly on the north and west facades.

#### Materials and Colour

- Examples of approved materials (but not limited to) are:
  - Brick,
  - Worked Canterbury stone,
  - Limestone (Oamaru stone or equivalent),
  - Weatherboard (painted or stained),
  - Plaster (painted).
- Any proposed alternative materials need to contribute to the overall design of the house and be thoughtful rather than token.
- A suitable mix of cladding materials is considered important with one material being seen as primary
  at least one other secondary cladding material being used to reinforce the design forms. This
  secondary cladding should constitute at least 10% of the wall area.

#### Corner Sites

- A corner site may either be bounded by two roads, or a road and a public reserve or access way.
- Corner sites shall address both frontages as covered under exterior appearance section of these guidelines.
- The needs of outdoor living will need to be carefully considered on corner sites particularly when they are North or West facing boundaries. Landscape design is critical to the success of corner sites.

## Garages

- The garage should not dominate the front façade of the house.
- The garage door should not exceed six metres in width if facing the street and should be clad in a
  material which has regard to the main materials of the house.
- The garage door must not be of the same profile as the roofing material used on the house. For example if long run Colorsteel is used for the roof, the garage door cannot be the same.

### Driveways

- The driveway is to be laid out to minimise the amount of hard paving visible from the street. Consider keeping the area small or perhaps screening with evergreen planting to reduce the visual impact.
- Note: Driveway formation needs to comply with local authority planning regulations.

#### Flues

Any flue from a heating device shall be formed in accordance with the following provisions:

- 1. If the heating device is an open fire or solid fuel burner (subject to Local Authority consent) then the flue must be housed and enclosed within a chimney structure complimentary to the house design and roofline and specifically approved by the Developer at its sole discretion.
- 2. If the heating device is a gas emission only device, although it is still recommended it be housed in a chimney structure for aesthetic appeal, a flue only shall be permitted subject to it being painted the same colour as the roof and being complementary to the house design and roofline and specifically approved by the Developer at its sole discretion.

#### Ancillary Elements

- Solar panels are to be fixed and located so that they are discrete and not generally visible from the street or neighbouring property unless they are of a low profile type and set at the same pitch as the roof.
- Satellite dishes and aerials are to be located so that they are not visible from the street.
- Garden sheds, and accessory buildings whether permanent or temporary, are not to be located within the front yard.

### YOUR GARDEN

#### LANDSCAPE PLANNING

## **Objectives**

The landscape plan needs to contribute to the general greening of the subdivision by providing a good mix of structural trees and native planting. This will result in improved street appeal of the individual houses as well as general environmental benefits.

The landscape design should provide a suitable outdoor living space linked with an indoor living area and located to give privacy and protection from the prevailing winds.

#### Specific Requirements

- A landscape plan prepared by a professional landscape designer is to be submitted as part of the approval process.
- All external open spaces need to be completely landscaped by the planting of trees, hedges, shrubs, grass or other forms of landscape such as paving and decking.
- Native and low water tolerant plants are preferred in order to reduce the reliance on artificial watering. Planting of native species is encouraged where possible.

- Front yards are to be planted with a mix of native and structural specimens and solid paving for functional access.
- A minimum of one specimen tree shall be planted within the front yard for every 8m of street boundary length or part thereof.
- Landscape planting should contribute to the screening for wind privacy and shade.
- The landscape plan presented for approval needs to include details of the:
  - Location of specimen trees showing species and maximum mature height.
  - Areas of planting with schedule of species.
  - Areas of lawn.
  - Paths, drives and hard paved areas with specification of finished surfaces.
  - Location of fences and screen walls showing heights and specification of materials.
  - Location and details of any ancillary buildings or elements, any water features, sculptures,
     retaining walls, planters or other landscape structures.
- The adjoining grass berm is invariably subject to excessive wear and tear (and possibly damage)
  during the building process. Therefore upon completion of the initial house build the berm will need
  to be restored. This will likely include removing any surface residue left from the building process
  (eg. gravel & concrete etc) followed by re-seeding and establishing the grass.

### **Recommended Plantings**

Note: (N) indicates a native plant.

### **TREES**

- Kōwhai Sophora microphylla (N)
- Horoeka / Lancewood Pseudopanax crassifolius (N)
- Ti Kouka Cordyline australis (N)
- Magnolia grandiflora 'Little Gem'
- Liquidambar styraciflua 'Worplesdon
- Acer 'Bowhall'
- Banksia integrifolia
- Albizia julibrissin 'Rosea'
- Gleditsia
- Prunus species
- Laurus nobilis

#### **HEDGING**

- Kapuka / Kaupuka Griselinia littoralis 'Broadway Mint' and 'Canterbury' (N)
- Corokia 'Geenty's Green' (N)

- Akeake (Dodonaea viscosa) (N)
- Pittosporum species (N)
- Akiraho Olearia paniculata (N)

## **SHRUBS**

- Shrubby Tororaro Muehlenbeckia astonii (N)
- Hebe species (N)
- Tarata / Lemonwood Pittosporum eugenioides (N)
- Akiraho Olearia paniculate (N)
- Pseudopanax arboreus

## **LOW SHRUBS, GRASSES & GROUNDCOVERS**

- Muehlenbeckia axillaris (N)
- Hebe species (N)
- Turutu Dianella nigra (N)
- Phormium species (N)
- Dwarf Toe Toe Chionochloa flavicans (N)
- Renga Renga Arthropodium 'Matapouri Bay' (N)
- Kakaha Astelia chathamica 'Silver Spear' (N)
- Poa cita (N)
- Carex Testacea (N)
- Pittosporum 'Gold Ball' (N)
- Lavandula species
- Canna Lilies
- Choisya 'Aztec Pearl'
- Rosmarinus prostrata
- · Erica species
- Dianella Tasred
- Dianella 'Little Rev'

#### **FENCING**

## **Objectives**

Fencing is to be constructed to create a suitable level of privacy and shelter to the private outdoor living areas and to screen service courtyards.

Generally side and rear boundary fencing will be provided by the Developer. Normally these will be 1.8 metre high timber paling fences which extend along the internal boundaries to a point one metre back from the road boundary.

Streams and waterways will also be fenced by the Developer using standard pool fencing.

### Specific Requirements

- If you wish to fence your front boundary, it must be designed in accordance with the Te Whata Tuarua Restrictive Covenants.
- Hedges or planted screening are acceptable alternatives.
- All timber fencing must be stained or painted.
- Fencing in the forecourt shall incorporate an adjoining road side planted strip or other suitable adjacent planting(s) to soften the appearance of the fence. These plantings are to be of an appropriate height necessary to achieve the desired effect.
- Side fences should be set back approx. one metre from the corners of houses rather than flush with the front wall.
- The Service Court (recycling & rubbish bins, gas bottles, air conditioning units, clotheslines etc.) should be screened from public view i.e. with a non-transparent screen or fence/gate.

## YOUR ENVIRONMENT

Designing your house and garden with the environment in mind is a small but significant consideration that you can do to ensure that you, your children and your children's children can continue with the amenities that you enjoy now. By conserving our natural resources and planning for the future you are not only helping the environment but saving yourself money in the long term.

## Consider the following:

- Installation of the highest possible rating of insulation to floor, walls and ceilings.
- Sensible distribution of opening windows to provide adequate natural ventilation.
- Careful consideration given to verandas or eave overhangs to reduce excessive solar gain in summer but allow low winter sun in to heat the interior spaces.
- · Correct sizing of heat pump units to maximise energy efficiency.
- · Dual flush toilet cisterns.
- · Rainwater storage tanks for irrigation.
- Install 3.5 star or higher rated white goods.
- Plant vegetable gardens and fruit trees.

## PLAN APPROVAL APPLICATION – TE WHATA TUARUA LOT NUMBER: This document must be completed by the applicant and submitted with the necessary information. If the appropriate information is not supplied the application may be returned. Name of Applicant: Name of Owner (if different): Applicant's Postal Address: Work Phone: Mobile: Email: **HOUSE DETAILS:** What is the size of the Section (m<sup>2</sup>): What is the Total Floor area of the Dwelling (including attached garages and carports) What is the maximum height of the Dwelling (m) What is the Roof Pitch of the Dwelling (degrees) **ATTACHMENTS:** Please attach the following to accompany your application. Check (tick) Site Plan (with North Point) Floor Plan Front Rear & Side Elevations Roof Plan **EXTERIOR MATERIALS & COLOUR SCHEME: Primary Exterior Cladding** Secondary Exterior Cladding Roof Cladding

Exterior Colours: To be submitted in a format that shows the colours in combination

Colours Required: Roof, All Exterior Claddings, Window Joinery, Garage Door, Front Door.

## LANDSCAPING:

Please ensure the following is included and detailed on the Landscape Plan or by way of accompanying documentation:

	Check (tick)
Conceptual Landscape Plan	
Driveway Location & Surface Finish	
All Paths & Surface Finishes	
All Patios & Decks	
Service Court Location (clothesline, gas bottles, rubbish & recycling bins etc.)	
Planting Legend/Detail	
Specimen Trees (noting mature height)	
Letterbox Location	
Any Accessory Buildings (location, size, exterior cladding/roof etc.)	
Details of Any Other Features:	
FENCING:	
Location of all Fencing (if in the forecourt note the set-back distance from the road boundary)	
All Fencing Heights (note all different heights)	
Construction Materials	
Elevation Profile (transparent/non-transparent/or a combination)	
Non-transparent Service Court Screen/Fence/Gate	

## **IMPORTANT INFORMATION:**

The Developer will endeavour to process all complying applications within five (5) working days.

The Approval of all applications is at the Developers sole discretion.

The Developer reserves the right to decline a House Plan and/or Exterior Colour Approval, even if it complies with the Restrictive Covenants and Design Guidelines, if the design or colours are not in keeping with the standard of the development or the proposed design, materials or colours have already been used too often either within the development or in close proximity of the subject site.